RC03II-1509
RC03II-1512

- High speed router,high cutting speed
- Multi-diameter router blade,wide application
- Configuration of spring cutter, lettering cutter, flexible pen set, etc
- Vacuum absorption
- LCD display key screen with EN&CN languages
- JWEI New pattern design software version 4.0

Garment Pattern

Intelligent cutting solution

Our innovation. Your success.

T-CUTTER
RC03II-1509
RC03II-1512

Finished Pattern samples

Sleeve

Pocket

Shoulder

Collar


Collar band

Convergent

Pocket cover

Application



Tools

Router tool

Carving tool

Spring cutting tool

Flexible pen set tool

Parameters

JWEI reserves the right of final interpretation of the following parameters, subject to change without prior notice.

Model	RC03II-1509	RC03II-1512
Working mode	Compatible with market general clothing CAD, computer operation and cutting at the same time, fast completion of data transmission	
Cutting mode	Multi diameter router (replaceable),carving tool, plotter	
Router diameter	3.175mm、4.3mm、6mm、8mm	
Maximum cutting speed	800mm/s (depends on different kinds of materials)	
Maximum cutting thickness	10mm	
Cutting materials	PVC board, acrylic board, MDF, plastic board hard materials, kraft paper, ivory cardboard	
Repeat precision	±0.1mm	
Rated Capacity	3.88kVA	3.88kVA
Maximum spindle motor speed	30000 (r/min)	
Material fixation mode	Vacuum suction	
Data transmission mode	HP-GL compatible mode	
Operation panel	LCD display key screen with EN&CN languages	
Drive system	Hybrid stepper motor, high precision linear guide, synchronous belt	
Rated voltage	AC 380V±10%50Hz(case power supply AC 220V)	
Machine Weight	250kG	280kG
Effective cutting area	1500mm×900mm	1500mm×1200mm
Machine size	2220mm×1620mm×1300mm	2220mm×1920mm×1300mm

NINGBO JINGWEI SYSTEMTECHNIK LTD.

Address: No. 1206, Jianlan Road, Yinzhou District, 315040, Ningbo, China

Hotline: +86 574 87913531 87900713 | Email: info@jingwei.com.cn | www.jweicut.com